

**TRACY HILLS SPECIFIC PLAN
DRAFT SUBSEQUENT ENVIRONMENTAL IMPACT REPORT
VOLUME II
DECEMBER 2014**

**APPENDIX H-4
HIGHWAY RAMP MERGE/DIVERGE ANALYSIS (HCS), DATED FALL
2014**

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Existing		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1			<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250			<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L _{up} = ft		Deceleration Lane Length L _D						L _{down} = ft	
V _u = veh/h		Freeway Volume, V _F			178			V _D = veh/h	
		Ramp Volume, V _R			41				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	178	0.92	Level	18	0	0.917	1.00	211	
Ramp	41	0.70	Level	11	0	0.948	1.00	62	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 211 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	273	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	273	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 6.0 (pc/mi/ln) LOS = A (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.299 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.6 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.6 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Existing				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			178		V _D = veh/h		
		Ramp Volume, V _R			58				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	178	0.92	Level	18	0	0.917	1.00	211	
Ramp	58	0.69	Level	19	0	0.913	1.00	92	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 211 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	211	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	119	Exhibit 13-8	4800	No
					V _R	92	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	211	Exhibit 13-8		4400:All
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 4.3 (pc/mi/ln) LOS = A (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.436 (Exhibit 13-12) S _R = 57.8 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.8 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580/Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Existing				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1689		V _D = veh/h		
		Ramp Volume, V _R			325				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1689	0.92	Level	18	0	0.917	1.00	2001	
Ramp	325	0.72	Level	13	0	0.939	1.00	481	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 2001 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2482	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2482	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 22.1 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.324 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	60.9 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	60.9 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Existing				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1886		V _D = veh/h		
		Ramp Volume, V _R			197				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1886	0.92	Level	18	0	0.917	1.00	2235	
Ramp	197	0.77	Level	14	0	0.935	1.00	274	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2235 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2235	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1961	Exhibit 13-8	4800	No
					V _R	274	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2235	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 21.7 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.453 (Exhibit 13-12) S _R = 57.3 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.3 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580/Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Existing				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1433		V _D = veh/h		
		Ramp Volume, V _R			333				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1433	0.92	Level	18	0	0.917	1.00	1698	
Ramp	333	0.86	Level	6	0	0.971	1.00	399	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1698 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2097	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2097	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 20.1 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.325 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	60.9 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	60.9 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Existing				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1433		V _D = veh/h		
		Ramp Volume, V _R			263				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1433	0.92	Level	18	0	0.917	1.00	1698	
Ramp	263	0.91	Level	8	0	0.962	1.00	301	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 1698 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1698	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1397	Exhibit 13-8	4800	No
					V _R	301	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1698	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 17.1 (pc/mi/ln) LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.455 (Exhibit 13-12) S _R = 57.3 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.3 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 WB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		PM Peak			Analysis Year		Existing		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1			<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400			<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L _{up} = ft		Deceleration Lane Length L _D						L _{down} = ft	
V _u = veh/h		Freeway Volume, V _F			967			V _D = veh/h	
		Ramp Volume, V _R			86				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	967	0.92	Level	18	0	0.917	1.00	1146	
Ramp	86	0.83	Level	5	0	0.976	1.00	106	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1146 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	1252	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	1252	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 12.7 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.291 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.9 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.9 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Existing				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1019		V _D = veh/h		
		Ramp Volume, V _R			52				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1019	0.92	Level	18	0	0.917	1.00	1207	
Ramp	52	0.93	Level	4	0	0.980	1.00	57	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 1207 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1207	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1150	Exhibit 13-8	4800	No
					V _R	57	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1207	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 12.8 (pc/mi/ln) LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.433 (Exhibit 13-12) S _R = 57.9 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.9 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Existing Plus Project		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			178		V _D = veh/h		
		Ramp Volume, V _R			221				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	178	0.92	Level	18	0	0.917	1.00	211	
Ramp	221	0.70	Level	11	0	0.948	1.00	333	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 211 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	544	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	544	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 8.0 (pc/mi/ln) LOS = A (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.300 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.6 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.6 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Existing Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			420		V _D = veh/h		
		Ramp Volume, V _R			242				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	420	0.92	Level	18	0	0.917	1.00	498	
Ramp	242	0.69	Level	19	0	0.913	1.00	384	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 498 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	498	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	114	Exhibit 13-8	4800	No
					V _R	384	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	498	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 6.7 (pc/mi/ln) LOS = A (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.463 (Exhibit 13-12) S _R = 57.0 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.0 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 WB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Existing Plus Project		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1689		V _D = veh/h		
		Ramp Volume, V _R			1171				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1689	0.92	Level	18	0	0.917	1.00	2001	
Ramp	1171	0.72	Level	13	0	0.939	1.00	1732	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 2001 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	3733	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	3733	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 31.3 (pc/mi/ln) LOS = D (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.440 (Exhibit 13-11) S _R = 57.7 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 57.7 mph (Exhibit 13-13)					D _s = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Existing Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1960		V _D = veh/h		
		Ramp Volume, V _R			271				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1960	0.92	Level	18	0	0.917	1.00	2322	
Ramp	271	0.77	Level	14	0	0.935	1.00	377	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2322 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2322	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R		1945	Exhibit 13-8	4800	No	
			V _R		377	Exhibit 13-10	2000	No	
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2322	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 22.4 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.462 (Exhibit 13-12) S _R = 57.1 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.1 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580/Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Existing Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1433		V _D = veh/h		
		Ramp Volume, V _R			449				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1433	0.92	Level	18	0	0.917	1.00	1698	
Ramp	449	0.86	Level	6	0	0.971	1.00	538	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1698 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2236	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2236	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 21.1 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.330 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	60.8 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	60.8 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Existing Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2455		V _D = veh/h		
		Ramp Volume, V _R			1022				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2455	0.92	Level	18	0	0.917	1.00	2909	
Ramp	1022	0.91	Level	8	0	0.962	1.00	1168	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2909 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2909	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R		1741	Exhibit 13-8	4800	No	
			V _R		1168	Exhibit 13-10	2000	No	
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2909	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 27.5 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.533 (Exhibit 13-12) S _R = 55.1 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 55.1 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 WB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		PM Peak			Analysis Year		Existing Plus Project		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			967		V _D = veh/h		
		Ramp Volume, V _R			326				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	967	0.92	Level	18	0	0.917	1.00	1146	
Ramp	326	0.83	Level	5	0	0.976	1.00	403	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1146 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	1549	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	1549	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 14.9 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.295 (Exhibit 13-11) S _R = 61.7 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 61.7 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Existing Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1178		V _D = veh/h		
		Ramp Volume, V _R			211				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1178	0.92	Level	18	0	0.917	1.00	1396	
Ramp	211	0.93	Level	4	0	0.980	1.00	231	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 1396 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1396	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R		1165	Exhibit 13-8	4800	No	
			V _R		231	Exhibit 13-10	2000	No	
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1396	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 14.5 (pc/mi/ln) LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.449 (Exhibit 13-12) S _R = 57.4 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.4 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 WB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Existing+Project Mitigated		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1689		V _D = veh/h		
		Ramp Volume, V _R			425				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1689	0.92	Level	18	0	0.917	1.00	2001	
Ramp	425	0.72	Level	13	0	0.939	1.00	629	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 2001 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2630	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2630	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 23.2 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.331 (Exhibit 13-11) S _R = 60.7 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 60.7 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580/Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Existing+Project Mitigated				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			967		V _D = veh/h		
		Ramp Volume, V _R			223				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	967	0.92	Level	18	0	0.917	1.00	1146	
Ramp	223	0.83	Level	5	0	0.976	1.00	275	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1146 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	1421	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	1421	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 13.9 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.293 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.8 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.8 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580/Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Existing Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			178		V _D = veh/h		
		Ramp Volume, V _R			279				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	178	0.92	Level	18	0	0.917	1.00	211	
Ramp	279	0.70	Level	11	0	0.948	1.00	420	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 211 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	631	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	631	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 8.6 (pc/mi/ln) LOS = A (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.301 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.6 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.6 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580 and Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Existing Plus Buildout		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			540		V _D = veh/h		
		Ramp Volume, V _R			362				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	540	0.92	Level	18	0	0.917	1.00	640	
Ramp	362	0.69	Level	19	0	0.913	1.00	574	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 640 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	640	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	66	Exhibit 13-8	4800	No
					V _R	574	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	640	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 8.0 (pc/mi/ln) LOS = A (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.480 (Exhibit 13-12) S _R = 56.6 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 56.6 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580/Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Existing Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1689		V _D = veh/h		
		Ramp Volume, V _R			1404				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1689	0.92	Level	18	0	0.917	1.00	2001	
Ramp	1404	0.72	Level	13	0	0.939	1.00	2077	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 2001 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	4078	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	4078	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 33.8 (pc/mi/ln) LOS = D (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.507 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	55.8 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	55.8 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Existing Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2024		V _D = veh/h		
		Ramp Volume, V _R			335				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2024	0.92	Level	18	0	0.917	1.00	2398	
Ramp	335	0.77	Level	14	0	0.935	1.00	466	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2398 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2398	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R		1932	Exhibit 13-8	4800	No	
			V _R		466	Exhibit 13-10	2000	No	
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2398	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 23.1 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.470 (Exhibit 13-12) S _R = 56.8 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 56.8 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		PM Peak			Analysis Year		Existing Plus Buildout		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1433		V _D = veh/h		
		Ramp Volume, V _R			699				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1433	0.92	Level	18	0	0.917	1.00	1698	
Ramp	699	0.86	Level	6	0	0.971	1.00	837	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1698 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2535	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2535	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 23.3 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.343 (Exhibit 13-11) S _R = 60.4 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 60.4 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Existing Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2525		V _D = veh/h		
		Ramp Volume, V _R			1092				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2525	0.92	Level	18	0	0.917	1.00	2992	
Ramp	1092	0.91	Level	8	0	0.962	1.00	1248	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2992 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2992	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1744	Exhibit 13-8	4800	No
					V _R	1248	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2992	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 28.2 (pc/mi/ln) LOS = D (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.540 (Exhibit 13-12) S _R = 54.9 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 54.9 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580/Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Existing Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp	Freeway Number of Lanes, N			2		Downstream Adj Ramp			
<input type="checkbox"/> Yes <input type="checkbox"/> On	Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On			
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off			
L _{up} = ft	Deceleration Lane Length L _D					L _{down} = ft			
V _u = veh/h	Freeway Volume, V _F			967		V _D = veh/h			
	Ramp Volume, V _R			686					
	Freeway Free-Flow Speed, S _{FF}			70.0					
	Ramp Free-Flow Speed, S _{FR}			55.0					
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	967	0.92	Level	18	0	0.917	1.00	1146	
Ramp	686	0.83	Level	5	0	0.976	1.00	847	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1146 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	1993	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	1993	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 18.1 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.306 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.4 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.4 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Existing Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1248		V _D = veh/h		
		Ramp Volume, V _R			281				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1248	0.92	Level	18	0	0.917	1.00	1479	
Ramp	281	0.93	Level	4	0	0.980	1.00	308	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 1479 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1479	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R		1171	Exhibit 13-8	4800	No	
			V _R		308	Exhibit 13-10	2000	No	
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1479	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 15.2 (pc/mi/ln) LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.456 (Exhibit 13-12) S _R = 57.2 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.2 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Existing+Buildout Mitigated				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			2		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			540		V _D = veh/h		
		Ramp Volume, V _R			362				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	540	0.92	Level	18	0	0.917	1.00	640	
Ramp	362	0.69	Level	19	0	0.913	1.00	574	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 640 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	640	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	66	Exhibit 13-8	4800	No
					V _R	574	Exhibit 13-10	4000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	640	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 1.7 (pc/mi/ln) LOS = A (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11)					D _S = 0.480 (Exhibit 13-12)				
S _R = mph (Exhibit 13-11)					S _R = 56.6 mph (Exhibit 13-12)				
S ₀ = mph (Exhibit 13-11)					S ₀ = N/A mph (Exhibit 13-12)				
S = mph (Exhibit 13-13)					S = 56.6 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Existing+Buildout Mitigated				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			2		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1092		V _D = veh/h		
		Ramp Volume, V _R			2525				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1092	0.92	Level	18	0	0.917	1.00	1294	
Ramp	2525	0.91	Level	8	0	0.962	1.00	2886	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 1294 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1294	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	-1592	Exhibit 13-8	4800	No
					V _R	2886	Exhibit 13-10	4000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1294	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 7.3 (pc/mi/ln) LOS = A (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.688 (Exhibit 13-12) S _R = 50.7 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 50.7 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 WB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Existing+Buildout Mitigated		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1689		V _D = veh/h		
		Ramp Volume, V _R			648				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1689	0.92	Level	18	0	0.917	1.00	2001	
Ramp	648	0.72	Level	13	0	0.939	1.00	958	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 2001 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2959	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2959	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 25.6 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.352 (Exhibit 13-11) S _R = 60.1 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 60.1 mph (Exhibit 13-13)					D _s = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 WB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		PM Peak			Analysis Year		Existing+Buildout Mitigated		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			967		V _D = veh/h		
		Ramp Volume, V _R			543				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	967	0.92	Level	18	0	0.917	1.00	1146	
Ramp	543	0.83	Level	5	0	0.976	1.00	671	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1146 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	1817	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	1817	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 16.8 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.301 (Exhibit 13-11) S _R = 61.6 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 61.6 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Cumulative		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			38		V _D = veh/h		
		Ramp Volume, V _R			109				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	38	0.92	Level	18	0	0.917	1.00	45	
Ramp	109	0.70	Level	11	0	0.948	1.00	164	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 45 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	209	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	209	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 5.5 (pc/mi/ln) LOS = A (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.298 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.6 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.6 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580/Lammers Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Cumulative		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			174		V _D = veh/h		
		Ramp Volume, V _R			41				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	174	0.92	Level	18	0	0.917	1.00	206	
Ramp	41	0.70	Level	11	0	0.948	1.00	62	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 206 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	268	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	268	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 6.0 (pc/mi/ln) LOS = A (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.299 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.6 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.6 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			215		V _D = veh/h		
		Ramp Volume, V _R			177				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	215	0.92	Level	18	0	0.917	1.00	255	
Ramp	177	0.69	Level	19	0	0.913	1.00	281	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 255 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	255	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	-26	Exhibit 13-8	4800	No
					V _R	281	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	255	Exhibit 13-8		4400:All
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 4.6 (pc/mi/ln) LOS = A (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.453 (Exhibit 13-12) S _R = 57.3 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.3 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET										
General Information					Site Information					
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB					
Agency or Company				Junction	I-580 and Lammers Road					
Date Performed	8/14/2014			Jurisdiction						
Analysis Time Period	AM Peak			Analysis Year	Cumulative					
Project Description Tracy Hills Specific Plan										
Inputs										
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp			
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On			
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off			
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft			
V _u = veh/h		Freeway Volume, V _F			236		V _D = veh/h			
		Ramp Volume, V _R			62					
		Freeway Free-Flow Speed, S _{FF}			70.0					
		Ramp Free-Flow Speed, S _{FR}			35.0					
Conversion to pc/h Under Base Conditions										
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p		
Freeway	236	0.92	Level	18	0	0.917	1.00	280		
Ramp	62	0.69	Level	19	0	0.913	1.00	98		
UpStream										
DownStream										
Merge Areas					Diverge Areas					
Estimation of v₁₂					Estimation of v₁₂					
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 280 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					
Capacity Checks					Capacity Checks					
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?	
V _{FO}		Exhibit 13-8			V _F	280	Exhibit 13-8	4800	No	
					V _{FO} = V _F - V _R	182	Exhibit 13-8	4800	No	
					V _R	98	Exhibit 13-10	2000	No	
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area					
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?	
V _{R12}		Exhibit 13-8			V ₁₂	280	Exhibit 13-8		4400:All	No
Level of Service Determination (if not F)					Level of Service Determination (if not F)					
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 4.9 (pc/mi/ln) LOS = A (Exhibit 13-2)					
Speed Determination					Speed Determination					
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.437 (Exhibit 13-12) S _R = 57.8 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.8 mph (Exhibit 13-13)					

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 WB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Cumulative		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1073		V _D = veh/h		
		Ramp Volume, V _R			622				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1073	0.92	Level	18	0	0.917	1.00	1271	
Ramp	622	0.72	Level	13	0	0.939	1.00	920	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1271 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2191	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2191	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 19.6 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.312 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.3 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.3 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 WB		
Agency or Company					Junction		I-580/Lammers Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Cumulative		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2			Downstream Adj Ramp	
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1			<input type="checkbox"/> Yes <input type="checkbox"/> On	
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400			<input checked="" type="checkbox"/> No <input type="checkbox"/> Off	
L _{up} = ft		Deceleration Lane Length L _D						L _{down} = ft	
V _u = veh/h		Freeway Volume, V _F			1583			V _D = veh/h	
		Ramp Volume, V _R			112				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1583	0.92	Level	18	0	0.917	1.00	1876	
Ramp	112	0.72	Level	13	0	0.939	1.00	166	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1876 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2042	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2042	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 18.8 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.307 (Exhibit 13-11) S _R = 61.4 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 61.4 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1545		V _D = veh/h		
		Ramp Volume, V _R			472				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1545	0.92	Level	18	0	0.917	1.00	1830	
Ramp	472	0.77	Level	14	0	0.935	1.00	656	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 1830 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1830	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1174	Exhibit 13-8	4800	No
					V _R	656	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1830	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 18.2 (pc/mi/ln) LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.487 (Exhibit 13-12) S _R = 56.4 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 56.4 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1695		V _D = veh/h		
		Ramp Volume, V _R			112				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1695	0.92	Level	18	0	0.917	1.00	2008	
Ramp	112	0.77	Level	14	0	0.935	1.00	156	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L _{EQ} =					L _{EQ} =				
P _{FM} =					P _{FD} =				
V ₁₂ =					V ₁₂ =				
V ₃ or V _{av34}					V ₃ or V _{av34}				
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
If Yes, V _{12a} =					If Yes, V _{12a} =				
pc/h (Equation 13-16, 13-18, or 13-19)					pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2008	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1852	Exhibit 13-8	4800	No
					V _R	156	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2008	Exhibit 13-8		4400:All
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
D _R = 5.475 + 0.00734 v _R + 0.0078 V ₁₂ - 0.00627 L _A					D _R = 4.252 + 0.0086 V ₁₂ - 0.009 L _D				
D _R = (pc/mi/ln)					D _R = 19.7 (pc/mi/ln)				
LOS = (Exhibit 13-2)					LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11)					D _S = 0.442 (Exhibit 13-12)				
S _R = mph (Exhibit 13-11)					S _R = 57.6 mph (Exhibit 13-12)				
S ₀ = mph (Exhibit 13-11)					S ₀ = N/A mph (Exhibit 13-12)				
S = mph (Exhibit 13-13)					S = 57.6 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		PM Peak			Analysis Year		Cumulative		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1567		V _D = veh/h		
		Ramp Volume, V _R			695				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1567	0.92	Level	18	0	0.917	1.00	1857	
Ramp	695	0.86	Level	6	0	0.971	1.00	832	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1857 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2689	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2689	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 24.5 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.351 (Exhibit 13-11) S _R = 60.2 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 60.2 mph (Exhibit 13-13)					D _s = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates				Freeway/Dir of Travel	I-580 EB			
Agency or Company					Junction	I-580/Lammers Road			
Date Performed	8/14/2014				Jurisdiction				
Analysis Time Period	PM Peak				Analysis Year	Cumulative			
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1806		V _D = veh/h		
		Ramp Volume, V _R			252				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1806	0.92	Level	18	0	0.917	1.00	2140	
Ramp	252	0.86	Level	6	0	0.971	1.00	302	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 2140 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2442	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2442	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 22.8 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.338 (Exhibit 13-11) S _R = 60.5 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 60.5 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2058		V _D = veh/h		
		Ramp Volume, V _R			491				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2058	0.92	Level	18	0	0.917	1.00	2438	
Ramp	491	0.91	Level	2	0	0.990	1.00	545	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2438 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2438	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R		1893	Exhibit 13-8	4800	No	
			V _R		545	Exhibit 13-10	2000	No	
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2438	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 23.4 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.477 (Exhibit 13-12) S _R = 56.6 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 56.6 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2118		V _D = veh/h		
		Ramp Volume, V _R			312				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2118	0.92	Level	18	0	0.917	1.00	2509	
Ramp	312	0.91	Level	2	0	0.990	1.00	346	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2509 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2509	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R			2163	Exhibit 13-8	4800	No
			V _R			346	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2509	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 24.0 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.459 (Exhibit 13-12) S _R = 57.1 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.1 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 WB		
Agency or Company					Junction		I-580/Corral Hollow		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		PM Peak			Analysis Year		Cumulative		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1139		V _D = veh/h		
		Ramp Volume, V _R			271				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1139	0.92	Level	18	0	0.917	1.00	1349	
Ramp	271	0.83	Level	7	0	0.966	1.00	338	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1349 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	1687	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	1687	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 16.0 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.298 (Exhibit 13-11) S _R = 61.7 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 61.7 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 WB		
Agency or Company					Junction		I-580/Lammers Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		PM Peak			Analysis Year		Cumulative		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1318		V _D = veh/h		
		Ramp Volume, V _R			246				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1318	0.92	Level	18	0	0.917	1.00	1562	
Ramp	246	0.83	Level	7	0	0.966	1.00	307	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1562 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	1869	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	1869	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 17.4 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.302 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.5 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.5 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1245		V _D = veh/h		
		Ramp Volume, V _R			106				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1245	0.92	Level	18	0	0.917	1.00	1475	
Ramp	106	0.93	Level	4	0	0.980	1.00	116	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 1475 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1475	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1359	Exhibit 13-8	4800	No
					V _R	116	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1475	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 15.1 (pc/mi/ln) LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.438 (Exhibit 13-12) S _R = 57.7 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.7 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1410		V _D = veh/h		
		Ramp Volume, V _R			92				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1410	0.92	Level	18	0	0.917	1.00	1671	
Ramp	92	0.93	Level	4	0	0.980	1.00	101	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L _{EQ} =					L _{EQ} =				
P _{FM} =					P _{FD} =				
V ₁₂ =					V ₁₂ =				
V ₃ or V _{av34}					V ₃ or V _{av34}				
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
If Yes, V _{12a} =					If Yes, V _{12a} =				
pc/h (Equation 13-16, 13-18, or 13-19)					pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1671	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1570	Exhibit 13-8	4800	No
					V _R	101	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1671	Exhibit 13-8		4400:All
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
D _R = 5.475 + 0.00734 v _R + 0.0078 V ₁₂ - 0.00627 L _A					D _R = 4.252 + 0.0086 V ₁₂ - 0.009 L _D				
D _R = (pc/mi/ln)					D _R = 16.8 (pc/mi/ln)				
LOS = (Exhibit 13-2)					LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11)					D _S = 0.437 (Exhibit 13-12)				
S _R = mph (Exhibit 13-11)					S _R = 57.8 mph (Exhibit 13-12)				
S ₀ = mph (Exhibit 13-11)					S ₀ = N/A mph (Exhibit 13-12)				
S = mph (Exhibit 13-13)					S = 57.8 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Cumulative Plus Buildout		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			67		V _D = veh/h		
		Ramp Volume, V _R			129				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	67	0.92	Level	18	0	0.917	1.00	79	
Ramp	129	0.70	Level	11	0	0.948	1.00	194	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 79 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	273	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	273	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 5.9 (pc/mi/ln) LOS = A (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.299 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.6 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.6 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580/Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			204		V _D = veh/h		
		Ramp Volume, V _R			70				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	204	0.92	Level	18	0	0.917	1.00	242	
Ramp	70	0.70	Level	11	0	0.948	1.00	106	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 242 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	348	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	348	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 6.6 (pc/mi/ln) LOS = A (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.299 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.6 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.6 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET										
General Information					Site Information					
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB					
Agency or Company				Junction	I-580 and Corral Hollow Road					
Date Performed	8/14/2014			Jurisdiction						
Analysis Time Period	AM Peak			Analysis Year	Cumulative Plus Project					
Project Description Tracy Hills Specific Plan										
Inputs										
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp			
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On			
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off			
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft			
V _u = veh/h		Freeway Volume, V _F			274		V _D = veh/h			
		Ramp Volume, V _R			207					
		Freeway Free-Flow Speed, S _{FF}			70.0					
		Ramp Free-Flow Speed, S _{FR}			35.0					
Conversion to pc/h Under Base Conditions										
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p		
Freeway	274	0.92	Level	18	0	0.917	1.00	325		
Ramp	207	0.69	Level	19	0	0.913	1.00	329		
UpStream										
DownStream										
Merge Areas					Diverge Areas					
Estimation of v₁₂					Estimation of v₁₂					
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 325 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					
Capacity Checks					Capacity Checks					
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?	
V _{FO}		Exhibit 13-8			V _F	325	Exhibit 13-8	4800	No	
					V _{FO} = V _F - V _R	-4	Exhibit 13-8	4800	No	
					V _R	329	Exhibit 13-10	2000	No	
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area					
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?	
V _{R12}		Exhibit 13-8			V ₁₂	325	Exhibit 13-8		4400:All	No
Level of Service Determination (if not F)					Level of Service Determination (if not F)					
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 5.2 (pc/mi/ln) LOS = A (Exhibit 13-2)					
Speed Determination					Speed Determination					
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.458 (Exhibit 13-12) S _R = 57.2 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.2 mph (Exhibit 13-13)					

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			355		V _D = veh/h		
		Ramp Volume, V _R			151				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	355	0.92	Level	18	0	0.917	1.00	421	
Ramp	151	0.69	Level	19	0	0.913	1.00	240	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 421 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	421	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	181	Exhibit 13-8	4800	No
					V _R	240	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	421	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 6.1 (pc/mi/ln) LOS = A (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.450 (Exhibit 13-12) S _R = 57.4 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.4 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580/Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1242		V _D = veh/h		
		Ramp Volume, V _R			702				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1242	0.92	Level	18	0	0.917	1.00	1472	
Ramp	702	0.72	Level	13	0	0.939	1.00	1038	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1472 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2510	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2510	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 22.1 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.325 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	60.9 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	60.9 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580/Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1663		V _D = veh/h		
		Ramp Volume, V _R			391				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1663	0.92	Level	18	0	0.917	1.00	1970	
Ramp	391	0.72	Level	13	0	0.939	1.00	578	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1970 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2548	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2548	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 22.6 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.327 (Exhibit 13-11) S _R = 60.8 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 60.8 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 WB		
Agency or Company					Junction		I-580 and Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Cumulative Plus Project		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1794		V _D = veh/h		
		Ramp Volume, V _R			552				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1794	0.92	Level	18	0	0.917	1.00	2126	
Ramp	552	0.77	Level	14	0	0.935	1.00	767	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2126 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2126	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1359	Exhibit 13-8	4800	No
					V _R	767	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2126	Exhibit 13-8		4400:All
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 20.7 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.497 (Exhibit 13-12) S _R = 56.1 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 56.1 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1944		V _D = veh/h		
		Ramp Volume, V _R			281				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1944	0.92	Level	18	0	0.917	1.00	2303	
Ramp	281	0.77	Level	14	0	0.935	1.00	390	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2303 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2303	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R	1913	Exhibit 13-8	4800	No		
			V _R	390	Exhibit 13-10	2000	No		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable	Violation?			Actual	Max Desirable	Violation?	
V _{R12}		Exhibit 13-8			V ₁₂	2303	Exhibit 13-8	4400:All	No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 22.3 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.463 (Exhibit 13-12) S _R = 57.0 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.0 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		PM Peak			Analysis Year		Cumulative Plus Project		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1666		V _D = veh/h		
		Ramp Volume, V _R			875				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1666	0.92	Level	18	0	0.917	1.00	1974	
Ramp	875	0.86	Level	6	0	0.971	1.00	1048	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1974 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	3022	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	3022	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 27.0 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.374 (Exhibit 13-11) S _R = 59.5 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 59.5 mph (Exhibit 13-13)					D _s = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580/Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1946		V _D = veh/h		
		Ramp Volume, V _R			351				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1946	0.92	Level	18	0	0.917	1.00	2306	
Ramp	351	0.86	Level	6	0	0.971	1.00	420	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 2306 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2726	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2726	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 25.0 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.353 (Exhibit 13-11) S _R = 60.1 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 60.1 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2297		V _D = veh/h		
		Ramp Volume, V _R			631				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2297	0.92	Level	18	0	0.917	1.00	2721	
Ramp	631	0.91	Level	2	0	0.990	1.00	700	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2721 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2721	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R	2021	Exhibit 13-8	4800	No		
			V _R	700	Exhibit 13-10	2000	No		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2721	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 25.9 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.491 (Exhibit 13-12) S _R = 56.3 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 56.3 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2527		V _D = veh/h		
		Ramp Volume, V _R			581				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2527	0.92	Level	18	0	0.917	1.00	2994	
Ramp	581	0.91	Level	2	0	0.990	1.00	645	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L _{EQ} =					L _{EQ} =				
P _{FM} =					P _{FD} =				
V ₁₂ =					V ₁₂ =				
V ₃ or V _{av34}					V ₃ or V _{av34}				
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
If Yes, V _{12a} =					If Yes, V _{12a} =				
pc/h (Equation 13-16, 13-18, or 13-19)					pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2994	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	2349	Exhibit 13-8	4800	No
					V _R	645	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2994	Exhibit 13-8		4400:All
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
D _R = 5.475 + 0.00734 v _R + 0.0078 V ₁₂ - 0.00627 L _A					D _R = 4.252 + 0.0086 V ₁₂ - 0.009 L _D				
D _R = (pc/mi/ln)					D _R = 28.2 (pc/mi/ln)				
LOS = (Exhibit 13-2)					LOS = D (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11)					D _S = 0.486 (Exhibit 13-12)				
S _R = mph (Exhibit 13-11)					S _R = 56.4 mph (Exhibit 13-12)				
S ₀ = mph (Exhibit 13-11)					S ₀ = N/A mph (Exhibit 13-12)				
S = mph (Exhibit 13-13)					S = 56.4 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 WB		
Agency or Company					Junction		I-580/Corral Hollow		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		PM Peak			Analysis Year		Cumulative Plus Project		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1198		V _D = veh/h		
		Ramp Volume, V _R			411				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1198	0.92	Level	18	0	0.917	1.00	1419	
Ramp	411	0.83	Level	7	0	0.966	1.00	513	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1419 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	1932	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	1932	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 17.8 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.304 (Exhibit 13-11) S _R = 61.5 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 61.5 mph (Exhibit 13-13)					D _s = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580/Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1458		V _D = veh/h		
		Ramp Volume, V _R			595				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1458	0.92	Level	18	0	0.917	1.00	1727	
Ramp	595	0.83	Level	7	0	0.966	1.00	742	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L _{EQ} =					L _{EQ} =				
P _{FM} = 1.000 using Equation (Exhibit 13-6)					P _{FD} = using Equation (Exhibit 13-7)				
V ₁₂ = 1727 pc/h					V ₁₂ = pc/h				
V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17)					V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17)				
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No				
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No				
If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2469	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2469	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$				
D _R = 21.9 (pc/mi/ln)					D _R = (pc/mi/ln)				
LOS = C (Exhibit 13-2)					LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.323 (Exhibit 13-11)					D _S = (Exhibit 13-12)				
S _R = 61.0 mph (Exhibit 13-11)					S _R = mph (Exhibit 13-12)				
S ₀ = N/A mph (Exhibit 13-11)					S ₀ = mph (Exhibit 13-12)				
S = 61.0 mph (Exhibit 13-13)					S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1404		V _D = veh/h		
		Ramp Volume, V _R			206				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1404	0.92	Level	18	0	0.917	1.00	1663	
Ramp	206	0.93	Level	4	0	0.980	1.00	226	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 1663 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1663	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R		1437	Exhibit 13-8	4800	No	
			V _R		226	Exhibit 13-10	2000	No	
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1663	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 16.8 (pc/mi/ln) LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.448 (Exhibit 13-12) S _R = 57.4 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.4 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative Plus Project				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1609		V _D = veh/h		
		Ramp Volume, V _R			151				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1609	0.92	Level	18	0	0.917	1.00	1906	
Ramp	151	0.93	Level	4	0	0.980	1.00	166	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 1906 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1906	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R			1740	Exhibit 13-8	4800	No
			V _R			166	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1906	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 18.8 (pc/mi/ln) LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.443 (Exhibit 13-12) S _R = 57.6 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.6 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative+Project Mitigated				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			2		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			355		V _D = veh/h		
		Ramp Volume, V _R			151				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	355	0.92	Level	18	0	0.917	1.00	421	
Ramp	151	0.69	Level	19	0	0.913	1.00	240	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 421 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	421	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	181	Exhibit 13-8	4800	No
					V _R	240	Exhibit 13-10	4000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	421	Exhibit 13-8	4400:All	No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = -0.2 (pc/mi/ln) LOS = A (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.450 (Exhibit 13-12) S _R = 57.4 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.4 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative+Project Mitigated				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			2		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2527		V _D = veh/h		
		Ramp Volume, V _R			581				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2527	0.92	Level	18	0	0.917	1.00	2994	
Ramp	581	0.91	Level	2	0	0.990	1.00	645	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2994 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2994	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	2349	Exhibit 13-8	4800	No
					V _R	645	Exhibit 13-10	4000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2994	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 21.9 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.486 (Exhibit 13-12) S _R = 56.4 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 56.4 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Cumulative Plus Buildout		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			87		V _D = veh/h		
		Ramp Volume, V _R			169				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	87	0.92	Level	18	0	0.917	1.00	103	
Ramp	169	0.70	Level	11	0	0.948	1.00	255	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 103 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	358	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	358	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 6.6 (pc/mi/ln) LOS = A (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.299 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.6 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.6 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580/Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			304		V _D = veh/h		
		Ramp Volume, V _R			90				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	304	0.92	Level	18	0	0.917	1.00	360	
Ramp	90	0.70	Level	11	0	0.948	1.00	136	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 360 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	496	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	496	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 7.7 (pc/mi/ln) LOS = A (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.300 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.6 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.6 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			394		V _D = veh/h		
		Ramp Volume, V _R			307				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	394	0.92	Level	18	0	0.917	1.00	467	
Ramp	307	0.69	Level	19	0	0.913	1.00	487	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 467 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	467	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	-20	Exhibit 13-8	4800	No
					V _R	487	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	467	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 6.5 (pc/mi/ln) LOS = A (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.472 (Exhibit 13-12) S _R = 56.8 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 56.8 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET										
General Information					Site Information					
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB					
Agency or Company				Junction	I-580 and Lammers Road					
Date Performed	8/14/2014			Jurisdiction						
Analysis Time Period	AM Peak			Analysis Year	Cumulative Plus Buildout					
Project Description Tracy Hills Specific Plan										
Inputs										
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp			
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On			
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off			
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft			
V _u = veh/h		Freeway Volume, V _F			475		V _D = veh/h			
		Ramp Volume, V _R			171					
		Freeway Free-Flow Speed, S _{FF}			70.0					
		Ramp Free-Flow Speed, S _{FR}			35.0					
Conversion to pc/h Under Base Conditions										
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p		
Freeway	475	0.92	Level	18	0	0.917	1.00	563		
Ramp	171	0.69	Level	19	0	0.913	1.00	271		
UpStream										
DownStream										
Merge Areas					Diverge Areas					
Estimation of v₁₂					Estimation of v₁₂					
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 563 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					
Capacity Checks					Capacity Checks					
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?	
V _{FO}		Exhibit 13-8			V _F	563	Exhibit 13-8	4800	No	
					V _{FO} = V _F - V _R	292	Exhibit 13-8	4800	No	
					V _R	271	Exhibit 13-10	2000	No	
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area					
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?	
V _{R12}		Exhibit 13-8			V ₁₂	563	Exhibit 13-8		4400:All	No
Level of Service Determination (if not F)					Level of Service Determination (if not F)					
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 7.3 (pc/mi/ln) LOS = A (Exhibit 13-2)					
Speed Determination					Speed Determination					
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.452 (Exhibit 13-12) S _R = 57.3 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.3 mph (Exhibit 13-13)					

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580/Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1262		V _D = veh/h		
		Ramp Volume, V _R			802				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1262	0.92	Level	18	0	0.917	1.00	1495	
Ramp	802	0.72	Level	13	0	0.939	1.00	1186	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1495 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2681	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2681	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 23.3 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.334 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	60.6 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	60.6 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580/Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1763		V _D = veh/h		
		Ramp Volume, V _R			421				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1763	0.92	Level	18	0	0.917	1.00	2089	
Ramp	421	0.72	Level	13	0	0.939	1.00	623	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 2089 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2712	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2712	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 23.8 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.336 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	60.6 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	60.6 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1874		V _D = veh/h		
		Ramp Volume, V _R			612				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1874	0.92	Level	18	0	0.917	1.00	2220	
Ramp	612	0.77	Level	14	0	0.935	1.00	850	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2220 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2220	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R	1370	Exhibit 13-8	4800	No		
			V _R	850	Exhibit 13-10	2000	No		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2220	Exhibit 13-8	4400:All	No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 21.5 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.505 (Exhibit 13-12) S _R = 55.9 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 55.9 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2064		V _D = veh/h		
		Ramp Volume, V _R			301				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2064	0.92	Level	18	0	0.917	1.00	2445	
Ramp	301	0.77	Level	14	0	0.935	1.00	418	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2445 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2445	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	2027	Exhibit 13-8	4800	No
					V _R	418	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2445	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 23.5 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.466 (Exhibit 13-12) S _R = 57.0 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.0 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580/Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1706		V _D = veh/h		
		Ramp Volume, V _R			985				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1706	0.92	Level	18	0	0.917	1.00	2021	
Ramp	985	0.86	Level	6	0	0.971	1.00	1180	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L _{EQ} =					L _{EQ} =				
P _{FM} = 1.000 using Equation (Exhibit 13-6)					P _{FD} = using Equation (Exhibit 13-7)				
V ₁₂ = 2021 pc/h					V ₁₂ = pc/h				
V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17)					V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17)				
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No				
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No				
If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	3201	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	3201	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$				
D _R = 28.3 (pc/mi/ln)					D _R = (pc/mi/ln)				
LOS = D (Exhibit 13-2)					LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.389 (Exhibit 13-11)					D _S = (Exhibit 13-12)				
S _R = 59.1 mph (Exhibit 13-11)					S _R = mph (Exhibit 13-12)				
S ₀ = N/A mph (Exhibit 13-11)					S ₀ = mph (Exhibit 13-12)				
S = 59.1 mph (Exhibit 13-13)					S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		PM Peak			Analysis Year		Existing		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1433		V _D = veh/h		
		Ramp Volume, V _R			333				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1433	0.92	Level	18	0	0.917	1.00	1698	
Ramp	333	0.86	Level	6	0	0.971	1.00	399	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1698 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2097	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2097	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 20.1 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.325 (Exhibit 13-11) S _R = 60.9 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 60.9 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2547		V _D = veh/h		
		Ramp Volume, V _R			841				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2547	0.92	Level	18	0	0.917	1.00	3018	
Ramp	841	0.91	Level	2	0	0.990	1.00	933	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L _{EQ} =					L _{EQ} =				
P _{FM} =					P _{FD} =				
V ₁₂ =					V ₁₂ =				
V ₃ or V _{av34}					V ₃ or V _{av34}				
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
If Yes, V _{12a} =					If Yes, V _{12a} =				
pc/h (Equation 13-16, 13-18, or 13-19)					pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	3018	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	2085	Exhibit 13-8	4800	No
					V _R	933	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	3018	Exhibit 13-8		4400:All
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
D _R = 5.475 + 0.00734 v _R + 0.0078 V ₁₂ - 0.00627 L _A					D _R = 4.252 + 0.0086 V ₁₂ - 0.009 L _D				
D _R = (pc/mi/ln)					D _R = 28.4 (pc/mi/ln)				
LOS = (Exhibit 13-2)					LOS = D (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11)					D _S = 0.512 (Exhibit 13-12)				
S _R = mph (Exhibit 13-11)					S _R = 55.7 mph (Exhibit 13-12)				
S ₀ = mph (Exhibit 13-11)					S ₀ = N/A mph (Exhibit 13-12)				
S = mph (Exhibit 13-13)					S = 55.7 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2757		V _D = veh/h		
		Ramp Volume, V _R			601				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2757	0.92	Level	18	0	0.917	1.00	3266	
Ramp	601	0.91	Level	2	0	0.990	1.00	667	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 3266 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	3266	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R		2599	Exhibit 13-8	4800	No	
			V _R		667	Exhibit 13-10	2000	No	
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	3266	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 30.5 (pc/mi/ln) LOS = D (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.488 (Exhibit 13-12) S _R = 56.3 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 56.3 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 WB		
Agency or Company					Junction		I-580/Corral Hollow		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		PM Peak			Analysis Year		Cumulative Plus Buildout		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1218		V _D = veh/h		
		Ramp Volume, V _R			691				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1218	0.92	Level	18	0	0.917	1.00	1443	
Ramp	691	0.83	Level	7	0	0.966	1.00	862	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1443 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2305	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2305	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 20.5 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.316 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.1 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.1 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580/Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1738		V _D = veh/h		
		Ramp Volume, V _R			685				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1738	0.92	Level	18	0	0.917	1.00	2059	
Ramp	685	0.83	Level	7	0	0.966	1.00	854	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 2059 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2913	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2913	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 25.3 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.349 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	60.2 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	60.2 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1484		V _D = veh/h		
		Ramp Volume, V _R			266				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1484	0.92	Level	18	0	0.917	1.00	1758	
Ramp	266	0.93	Level	4	0	0.980	1.00	292	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 1758 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1758	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1466	Exhibit 13-8	4800	No
					V _R	292	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1758	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 17.6 (pc/mi/ln) LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.454 (Exhibit 13-12) S _R = 57.3 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.3 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative Plus Buildout				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1909		V _D = veh/h		
		Ramp Volume, V _R			171				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1909	0.92	Level	18	0	0.917	1.00	2262	
Ramp	171	0.93	Level	4	0	0.980	1.00	188	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2262 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2262	Exhibit 13-8	4800	No
			V _{FO} = V _F - V _R		2074	Exhibit 13-8	4800	No	
			V _R		188	Exhibit 13-10	2000	No	
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2262	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 21.9 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.445 (Exhibit 13-12) S _R = 57.5 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.5 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580/Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative+Buildout Mitigated				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			2		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			87		V _D = veh/h		
		Ramp Volume, V _R			169				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	87	0.92	Level	18	0	0.917	1.00	103	
Ramp	169	0.70	Level	11	0	0.948	1.00	255	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 103 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	358	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	358	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 1.9 (pc/mi/ln) LOS = A (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.217 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	63.9 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	63.9 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580/Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative+Buildout Mitigated				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			2		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1706		V _D = veh/h		
		Ramp Volume, V _R			985				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1706	0.92	Level	18	0	0.917	1.00	2021	
Ramp	985	0.86	Level	6	0	0.971	1.00	1180	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 2021 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	3201	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	3201	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 23.6 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.307 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.4 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.4 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Cumulative+Buildout Mitigated				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			2		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			394		V _D = veh/h		
		Ramp Volume, V _R			307				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	394	0.92	Level	18	0	0.917	1.00	467	
Ramp	307	0.69	Level	19	0	0.913	1.00	487	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 467 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	467	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	-20	Exhibit 13-8	4800	No
					V _R	487	Exhibit 13-10	4000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	467	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 0.2 (pc/mi/ln) LOS = A (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.472 (Exhibit 13-12) S _R = 56.8 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 56.8 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative+Buildout Mitigated				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			2		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2547		V _D = veh/h		
		Ramp Volume, V _R			841				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2547	0.92	Level	18	0	0.917	1.00	3018	
Ramp	841	0.91	Level	2	0	0.990	1.00	933	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 3018 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	3018	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	2085	Exhibit 13-8	4800	No
					V _R	933	Exhibit 13-10	4000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	3018	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 22.1 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.512 (Exhibit 13-12) S _R = 55.7 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 55.7 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580 and Lammers Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Cumulative+Buildout Mitigated		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			2		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			475		V _D = veh/h		
		Ramp Volume, V _R			171				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	475	0.92	Level	18	0	0.917	1.00	563	
Ramp	171	0.69	Level	19	0	0.913	1.00	271	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 563 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	563	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	292	Exhibit 13-8	4800	No
					V _R	271	Exhibit 13-10	4000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	563	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 1.0 (pc/mi/ln) LOS = A (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.452 (Exhibit 13-12) S _R = 57.3 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.3 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Lammers Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Cumulative+Buildout Mitigated				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			2		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2757		V _D = veh/h		
		Ramp Volume, V _R			601				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2757	0.92	Level	18	0	0.917	1.00	3266	
Ramp	601	0.91	Level	2	0	0.990	1.00	667	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L _{EQ} =					L _{EQ} =				
P _{FM} =					P _{FD} =				
V ₁₂ =					V ₁₂ =				
V ₃ or V _{av34}					V ₃ or V _{av34}				
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
If Yes, V _{12a} =					If Yes, V _{12a} =				
pc/h (Equation 13-16, 13-18, or 13-19)					pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	3266	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	2599	Exhibit 13-8	4800	No
					V _R	667	Exhibit 13-10	4000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	3266	Exhibit 13-8		4400:All
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
D _R = 5.475 + 0.00734 v _R + 0.0078 V ₁₂ - 0.00627 L _A					D _R = 4.252 + 0.0086 V ₁₂ - 0.009 L _D				
D _R = (pc/mi/ln)					D _R = 24.2 (pc/mi/ln)				
LOS = (Exhibit 13-2)					LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11)					D _S = 0.488 (Exhibit 13-12)				
S _R = mph (Exhibit 13-11)					S _R = 56.3 mph (Exhibit 13-12)				
S ₀ = mph (Exhibit 13-11)					S ₀ = N/A mph (Exhibit 13-12)				
S = mph (Exhibit 13-13)					S = 56.3 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		AM Peak			Analysis Year		Existing Plus Phase IA		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			178		V _D = veh/h		
		Ramp Volume, V _R			74				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	178	0.92	Level	18	0	0.917	1.00	211	
Ramp	74	0.70	Level	11	0	0.948	1.00	112	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 211 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	323	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	323	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 6.4 (pc/mi/ln) LOS = A (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S =	0.299 (Exhibit 13-11)				D _S =	(Exhibit 13-12)			
S _R =	61.6 mph (Exhibit 13-11)				S _R =	mph (Exhibit 13-12)			
S ₀ =	N/A mph (Exhibit 13-11)				S ₀ =	mph (Exhibit 13-12)			
S =	61.6 mph (Exhibit 13-13)				S =	mph (Exhibit 13-13)			

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Existing Plus Phase I				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			339		V _D = veh/h		
		Ramp Volume, V _R			161				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	339	0.92	Level	18	0	0.917	1.00	402	
Ramp	161	0.69	Level	19	0	0.913	1.00	256	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 402 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	402	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	146	Exhibit 13-8	4800	No
					V _R	256	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	402	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 5.9 (pc/mi/ln) LOS = A (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.451 (Exhibit 13-12) S _R = 57.4 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.4 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580/Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Existing Plus Phase IA				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1689		V _D = veh/h		
		Ramp Volume, V _R			650				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1689	0.92	Level	18	0	0.917	1.00	2001	
Ramp	650	0.72	Level	13	0	0.939	1.00	961	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 2001 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2962	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2962	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 25.6 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.352 (Exhibit 13-11) S _R = 60.1 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 60.1 mph (Exhibit 13-13)					D _s = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	AM Peak			Analysis Year	Existing Plus Phase IA				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1921		V _D = veh/h		
		Ramp Volume, V _R			232				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1921	0.92	Level	18	0	0.917	1.00	2276	
Ramp	232	0.77	Level	14	0	0.935	1.00	322	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 2276 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2276	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1954	Exhibit 13-8	4800	No
					V _R	322	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2276	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 22.0 (pc/mi/ln) LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11)					D _S = 0.457 (Exhibit 13-12)				
S _R = mph (Exhibit 13-11)					S _R = 57.2 mph (Exhibit 13-12)				
S ₀ = mph (Exhibit 13-11)					S ₀ = N/A mph (Exhibit 13-12)				
S = mph (Exhibit 13-13)					S = 57.2 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst		Kimley-Horn & Associates			Freeway/Dir of Travel		I-580 EB		
Agency or Company					Junction		I-580/Corral Hollow Road		
Date Performed		8/14/2014			Jurisdiction				
Analysis Time Period		PM Peak			Analysis Year		Existing Plus Phase IA		
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			250		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1433		V _D = veh/h		
		Ramp Volume, V _R			397				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1433	0.92	Level	18	0	0.917	1.00	1698	
Ramp	397	0.86	Level	6	0	0.971	1.00	475	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v ₁₂					Estimation of v ₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1698 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	2173	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	2173	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 20.6 (pc/mi/ln) LOS = C (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.328 (Exhibit 13-11) S _R = 60.8 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 60.8 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 EB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Existing Plus Phase IA				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			2074		V _D = veh/h		
		Ramp Volume, V _R			641				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	2074	0.92	Level	18	0	0.917	1.00	2457	
Ramp	641	0.91	Level	8	0	0.962	1.00	733	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13)				
L _{EQ} =					L _{EQ} =				
P _{FM} =					P _{FD} =				
V ₁₂ =					V ₁₂ =				
V ₃ or V _{av34}					V ₃ or V _{av34}				
Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No					Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
If Yes, V _{12a} =					If Yes, V _{12a} =				
pc/h (Equation 13-16, 13-18, or 13-19)					pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	2457	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1724	Exhibit 13-8	4800	No
					V _R	733	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	2457	Exhibit 13-8		4400:All
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
D _R = 5.475 + 0.00734 v _R + 0.0078 V ₁₂ - 0.00627 L _A					D _R = 4.252 + 0.0086 V ₁₂ - 0.009 L _D				
D _R = (pc/mi/ln)					D _R = 23.6 (pc/mi/ln)				
LOS = (Exhibit 13-2)					LOS = C (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11)					D _S = 0.494 (Exhibit 13-12)				
S _R = mph (Exhibit 13-11)					S _R = 56.2 mph (Exhibit 13-12)				
S ₀ = mph (Exhibit 13-11)					S ₀ = N/A mph (Exhibit 13-12)				
S = mph (Exhibit 13-13)					S = 56.2 mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates				Freeway/Dir of Travel	I-580 WB			
Agency or Company					Junction	I-580/Corral Hollow Road			
Date Performed	8/14/2014				Jurisdiction				
Analysis Time Period	PM Peak				Analysis Year	Existing Plus Phase IA			
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A			400		<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D					L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			967		V _D = veh/h		
		Ramp Volume, V _R			663				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			55.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	967	0.92	Level	18	0	0.917	1.00	1146	
Ramp	663	0.83	Level	5	0	0.976	1.00	819	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = 1.000 using Equation (Exhibit 13-6) V ₁₂ = 1146 pc/h V ₃ or V _{av34} = 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = using Equation (Exhibit 13-7) V ₁₂ = pc/h V ₃ or V _{av34} = pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}	1965	Exhibit 13-8		No	V _F		Exhibit 13-8		
					V _{FO} = V _F - V _R		Exhibit 13-8		
					V _R		Exhibit 13-10		
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}	1965	Exhibit 13-8	4600:All	No	V ₁₂		Exhibit 13-8		
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = 17.9 (pc/mi/ln) LOS = B (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = 0.305 (Exhibit 13-11) S _R = 61.5 mph (Exhibit 13-11) S ₀ = N/A mph (Exhibit 13-11) S = 61.5 mph (Exhibit 13-13)					D _S = (Exhibit 13-12) S _R = mph (Exhibit 13-12) S ₀ = mph (Exhibit 13-12) S = mph (Exhibit 13-13)				

RAMPS AND RAMP JUNCTIONS WORKSHEET									
General Information					Site Information				
Analyst	Kimley-Horn & Associates			Freeway/Dir of Travel	I-580 WB				
Agency or Company				Junction	I-580 and Corral Hollow Road				
Date Performed	8/14/2014			Jurisdiction					
Analysis Time Period	PM Peak			Analysis Year	Existing Plus Phase IA				
Project Description Tracy Hills Specific Plan									
Inputs									
Upstream Adj Ramp		Freeway Number of Lanes, N			2		Downstream Adj Ramp		
<input type="checkbox"/> Yes <input type="checkbox"/> On		Ramp Number of Lanes, N			1		<input type="checkbox"/> Yes <input type="checkbox"/> On		
<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		Acceleration Lane Length, L _A					<input checked="" type="checkbox"/> No <input type="checkbox"/> Off		
L _{up} = ft		Deceleration Lane Length L _D			200		L _{down} = ft		
V _u = veh/h		Freeway Volume, V _F			1199		V _D = veh/h		
		Ramp Volume, V _R			232				
		Freeway Free-Flow Speed, S _{FF}			70.0				
		Ramp Free-Flow Speed, S _{FR}			35.0				
Conversion to pc/h Under Base Conditions									
(pc/h)	V (Veh/hr)	PHF	Terrain	%Truck	%Rv	f _{HV}	f _p	v = V/PHF x f _{HV} x f _p	
Freeway	1199	0.92	Level	18	0	0.917	1.00	1421	
Ramp	232	0.93	Level	4	0	0.980	1.00	254	
UpStream									
DownStream									
Merge Areas					Diverge Areas				
Estimation of v₁₂					Estimation of v₁₂				
$V_{12} = V_F (P_{FM})$ (Equation 13-6 or 13-7) L _{EQ} = P _{FM} = using Equation (Exhibit 13-6) V ₁₂ = pc/h V ₃ or V _{av34} pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)					$V_{12} = V_R + (V_F - V_R)P_{FD}$ (Equation 13-12 or 13-13) L _{EQ} = P _{FD} = 1.000 using Equation (Exhibit 13-7) V ₁₂ = 1421 pc/h V ₃ or V _{av34} 0 pc/h (Equation 13-14 or 13-17) Is V ₃ or V _{av34} > 2,700 pc/h? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Is V ₃ or V _{av34} > 1.5 * V ₁₂ /2 <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If Yes, V _{12a} = pc/h (Equation 13-16, 13-18, or 13-19)				
Capacity Checks					Capacity Checks				
	Actual	Capacity		LOS F?		Actual	Capacity		LOS F?
V _{FO}		Exhibit 13-8			V _F	1421	Exhibit 13-8	4800	No
					V _{FO} = V _F - V _R	1167	Exhibit 13-8	4800	No
					V _R	254	Exhibit 13-10	2000	No
Flow Entering Merge Influence Area					Flow Entering Diverge Influence Area				
	Actual	Max Desirable		Violation?		Actual	Max Desirable		Violation?
V _{R12}		Exhibit 13-8			V ₁₂	1421	Exhibit 13-8 4400:All		No
Level of Service Determination (if not F)					Level of Service Determination (if not F)				
$D_R = 5.475 + 0.00734 v_R + 0.0078 V_{12} - 0.00627 L_A$ D _R = (pc/mi/ln) LOS = (Exhibit 13-2)					$D_R = 4.252 + 0.0086 V_{12} - 0.009 L_D$ D _R = 14.7 (pc/mi/ln) LOS = B (Exhibit 13-2)				
Speed Determination					Speed Determination				
M _S = (Exhibit 13-11) S _R = mph (Exhibit 13-11) S ₀ = mph (Exhibit 13-11) S = mph (Exhibit 13-13)					D _S = 0.451 (Exhibit 13-12) S _R = 57.4 mph (Exhibit 13-12) S ₀ = N/A mph (Exhibit 13-12) S = 57.4 mph (Exhibit 13-13)				