Where Does Your Water Come From?

Sources of the City of Tracy's water supply include the Stanislaus River, the Delta-Mendota Canal, and groundwater pumped from wells. In 2011, surface water from the Stanislaus River comprised 70%, or 3.8 billion gallons. Surface water from the Delta-Mendota Canal comprised 28% of the total water supply, or 1.5 billion gallons. The groundwater supply comprised 2%, or 0.1 billion gallons of the total water supply. The Stanislaus River water supply is very soft water and has significantly reduced the minerals in the City's water supply. You may no longer need to use a water softener.



Water Quality Control

Before the water reaches your tap, samples are collected and tested in State-certified laboratories. The City of Tracy Utilities Division of the Public Works Department has a regular program of water quality monitoring and system inspection that ensures safe drinking water is delivered to you and your family.

As required by the Federal Safe Drinking Water Act, the City's water supplies must meet stringent water quality standards set by the California Department of Public Health and the United States Environmental Protection Agency. The City of Tracy completed a watershed sanitary survey of its drinking water sources in 2010. This survey can be obtained by contacting the Water Production Superintendent at the number provided below.

Water customers who are landlords receiving this report are asked to share this information with any tenant or user on the premises. The City of Tracy staff is available to answer your questions and provide further information. You are welcome to call the Water Production Superintendent at (209) 831-6302.

necessary to maintain the highest quality drinking water informed are our best allies in supporting improvements your water supply because customers who are well committed to providing you with this information about information to each of their customers annually. We are requiring water utilities to provide detailed water quality This publication conforms to the regulation under SDWA

states are enforcing the laws that regulate drinking water. consumers are receiving clean water and to verify that drinking water. USEPA uses this data to ensure that the Department of Public Health if they were detected in the substances and reports directly to the California substances. Each system continually monitors for these reatments that water systems must use to remove these substances in drinking water and also specifies various responsible for setting national limits for hundreds of Under the Safe Drinking Water Act (SDWA), USEPA is Safe Drinking Water Act



1674-624 Safe Drinking Water Hotline (800) contaminants are available from the

the risk of infection by Cryptosporidium and other microbial Disease Control) guidelines on appropriate means to lessen from their health care providers. USEPA/CDC (Center for tions. These people should seek advice about drinking water some elderly and infants, can be particularly at risk from infecplants, people with HIV/AIDS or other immune disorders, and chemotherapy, persons who have undergone organ transcompromised persons such as those with cancer undergoing drinking water than the general population. Immuno-Some people may be more vulnerable to contaminants in

Special Health Information





CITY OF TRACY

Think Inside the Triangle

We are pleased to report that during the past year, the water delivered to your home or business complied with, or exceeded, all state and federal drinking water requirements! We have compiled a table showing what substances were detected in our drinking water. Although all of the substances listed are under the maximum level allowable set by United States Environmental Protection Agency (USEPA), we feel it is important that you know exactly what was detected and how much of the substance was present in the water.

In California, drinking water standards, also called Maximum $\,$ Contaminant Levels (MCLs), are set in two categories: Primary Standards related to public health, and Secondary Standards which relate to the aesthetic qualities such as taste, odor, and color. Within you will find a complete listing of both types of standards along with the results of the analysis of your water supply.

www.water.ca.gov/drought/.

For more information on drought conditions visit http://

will assist the City in attaining water conservation goals! for longer than 8 minutes per cycle. You're continued efforts a.m.; never water landscaping on a windy day; and do not water lawns and landscapes between the hours of 9:00 p.m. and 7:00 turning off irrigation timers in the winter months; only water walks; using an automated carwash instead of hand washing; sweeping instead of rinsing off driveways, parking lots, or sideties. Simple outdoor water conservation measures to utilize are: The biggest use of water by homeowners is for outdoor activi-

changing out high water consuming appliances to more efficient reminding hotel guests to conserve water when showering, and might also consider offering water to customers only if asked, and always turning off water while brushing teeth. Businesses as a trash receptacle, repairing drips and leaking faucets quickly, shampooing, washing full loads of laundry, never using the toilet plement are: taking shorter showers, turning water off while the City. Some simple indoor measures homeowners may imconservation measures will need to be observed by everyone in ness owners in the future? It means that continued voluntary What does all this mean for the City of Tracy residents and busi-

to lower water consumption.

requesting voluntary measures from its consumers in an attempt conservation measures while others like the City of Tracy are level. Some local water agencies have already issued mandatory low water conservation measures to remain at this consumption duction goal in 2010 and 2011, and will need to continue to folthan 2020. The City of Tracy consumers achieved the 20% repalities must reduce their per capita water use by 20% no later California's 20×2020 Plan. This plan mandates that all municieffort to reduce water consumption and to meet the State of conservation efforts will be stepped up across the state in an In 2012, as California continues to face water supply shortages,

Water Conservation is Strongly Encouraged



USEPA's Safe Drinking Water Hotline (800) 426-4791. and potential health effects can be obtained by calling the water poses a health risk. More information about contaminants presence of contaminants does not necessarily indicate that the to contain at least small amounts of some contaminants. The ing water, including bottled water, may reasonably be expected that must provide the same protection for public health. Drinkregulations also establish limits for contaminants in bottled water by public water systems. California Department of Public Health that limit the amount of certain contaminants in water provided the California Department of Public Health prescribe regulations In order to ensure that the tap water is safe to drink, USEPA and

ring or be the result of oil and gas production and mining ac-Radio Active Contaminants, which can be naturally occurgas stations, urban runoff and septic systems;

processes and petroleum production, and can, also come from volatile organic chemicals, which are by-products of industrial Organic Chemical Contaminants, including synthetic and

of sources such as agriculture, urban storm water runoff, and Pesticides and Herbicides, which may come from a variety gas production, mining, or farming;

runoff, industrial or domestic wastewater discharges, oil and can be naturally occurring or result from urban storm water • Inorganic Contaminants, such as salts and metals, which

which may come from sewage treatment plants, septic sys-• Microbial Contaminants, such as viruses and bacteria,

tems, agricultural livestock operations, and wildlife;

that may be present in source water include: from the presence of animals or human activity. Contaminants cases, radioactive material, and can pick up substances resulting the ground, it dissolves naturally occurring minerals and, in some wells. As water travels over the surface of the land or through ter) include rivers, lakes, streams, ponds, reservoirs, springs and The sources of drinking water (both tap water and bottled wa-

Substances Expected to be in the Drinking Water



	TREATED SURFACE WATER	TREATED SURFACE WATER	WELL WATER			REGULATORY LIMITS		TYPICAL SOURCE
ANALYTICAL PARAMETER	SOUTH SAN JOAQUIN IRRIGATION DISTRICT	JOHN JONES WATER TREATMENT PLANT	AVERAGE	MINIMUM	MAXIMUM	MCLG or PHG	MAXIMUM CONTAMINANT LEVEL (MCL)	
PRIMARY STANDARDS								
INORGANIC (ug/L)								
Aluminum	ND	ND	156	31	280	none	1000 ug/L	Erosion of natural deposits
Arsenic	ND	ND	3	1	5	0	10 ug/L	Erosion of natural deposits
Barium	14.3	20	32	20	40	2000	1000 ug/L	Erosion of natural deposits
Chromium	ND	ND	5	-1	8	100	50 ug/L	Erosion of natural deposits
Copper	ND	ND	3	2	5	170	1000 ug/L	Erosion of natural deposits
Iron	ND	ND	240	34	880	NA	300 ug/L	Erosion of natural deposits
Manganese	ND	ND	52	7	100	NA NA	50 ug/L	Erosion of natural deposits
Nickel	1	ND	ND	ND	ND	100	100 ug/L	Erosion of natural deposits
NITRATE/NITRITE				,,,_			100 09:2	
Nitrate (as NO3) ¹	0.44	1.5	8	4	13	45	45 mg/L	Runoff from fertilizer use; Erosion of natural
Nitrate + Nitrite (sum as N)	0.1	0.34	2	1	3	10	10 mg/L	deposits
Nitrite (as N)	ND	ND	ND	ND	ND ND	1	1 mg/L	deposits
SECONDARY STANDARDS	1,42	1,12	1,0	IND	110		, nigr	
Aesthetic - Related								
Aluminum (ug/L)	ND	ND	104	ND	280	none	1000 ug/L	Erosion of natural deposits
Apparent Color (Units)	9	ND	3	3	3	NA	15 Units	Naturally occurring organic materials
Copper (ug/L)	ND	ND	3	ND	5	170	1000 ug/L	Erosion of natural deposits
Corrosivity Index	-1	-1.6	ND ND	ND	1	NA NA	Non-corrosive	Naturally occuring
0 8 8	ND	ND	200	ND ND	880	NA NA	300 ug/L	Erosion of natural deposits
Iron (ug/L)	ND	ND	41	ND ND	100	NA NA		
Manganese (ug/L)	ND ND	1	1	1	2	NA NA	50 ug/L 3 TON	Erosion of natural deposits
Odor (TON)	ND	1.4	3	2	4	NA NA	NS NS	Naturally occuring organic materials
Potassium (K) (mg/L) Turbidity (NTU) ²	0.3	0.074	1	ND ND	2		5244	Erosion of natural deposits
A-V: 90: HVPD:	ND	0.074 ND	ND	ND ND	ND	NA NA	5 NTU	Soil runoff
Zinc (ug/L)	50	48	l				5000 ug/L	Erosion of natural deposits
Bicarbonate (HCO3) (mg/L)	40	40	142 115	100 82	170 140	NA NA	NS NC	Erosion of natural deposits
Total Alkalinity (CaCO3)(mg/L)	ND	0.11	1	1	2	NA NA	NS NC	Erosion of natural deposits
Boron (B) (mg/L)	15	13		30	- 20		NS NC	Erosion of natural deposits
Calcium (Ca) (mg/L)	5	6.7	51 20	11100	75 34	NA NA	NS No	Erosion of natural deposits
Magnesium (Mg) (mg/L)	5	20	1000	12	2000	NA NA	NS NC	Erosion of natural deposits
Sodium (Na) (mg/L) Total Hardness (CaCO3) (mg/L)	58	61	103	88 120	130	NA NA	NS NC	Erosion of natural deposits
3524656C 3648C	110	140	590	440	320 830	NA NA	NS 1000 mm//	Erosion of natural deposits
TDS (mg/L) Specific Conductance (umhos/cm)	149	230	917	740	1200	NA NA	1000 mg/L 1600 umhos/cm	Erosion of natural deposits
the second secon	100.000	00000000		10. 000/	7.00000	1 1000		Substances that form ions when in water
Chloride (mg/L)	16 4	24 28	98	140	120	NA NA	500 mg/L	Erosion of natural deposits
Sulfate (mg/L)	7.6	8.6	202	140 7	290	NA NA	500 mg/L	Erosion of natural deposits
Н		OSWING.	8 BUTION OVOTEM DA	Discount contraction	8	NA	6.5 - 8.5 Units	NA
FOUR PROPERTY REPORT REPORT AND THE REPORT OF THE REPORT O			BUTION SYSTEM DA	IA SHEET				
BACTERIOLOGICAL (%	Present)	<1	<1	<1	<1	0	50/, Drocopt/mo	M
Coliform Density	1000	<u> </u>	- A36	Commence and the commence of t	18391	U	5% Present/mo.	Municipal and industrial waste discharge
ORGANICS (ug/L	J	-	RUNI	NING ANNUAL AVER	AUE	NA	00 000	Do annual control of distriction of the control of
Total Trihalomethane			39 22		NA NA	80 ug/L 60 ug/L	By-product of drinking water chlorination	
Total Halnacetic Acids				44		n NA	i uu uu/L	By-product of drinking water chlorination

1 Nitrate in drinking water at levels above 45 ppm is a health risk for infants of less than six months of age. Such nitrate levels in drinking water can interfere with the capacity of the infant's blood to carry oxygen, resulting in a serious illness; symptoms include shortness of breath and blueness of the skin. Nitrate levels above 45 ppm may also affect the ability of the blood to carry oxygen in other individuals, such as pregnant

DEFINITIONS

AL (Action Level): The concentration of a contaminant, which, if exceeded, triggers treatment or other requirements, which a water system must follow.

MCL (Maximum Contaminant Level): The highest level of a contaminant that is allowed in drinking water. Primary MCLs are set as close to the PHGs (or MCLGs) as is economically and technologically feasible.

Secondary MCLs (SMCL): Are set to protect the odor, taste, and appearance of drinking water.

MCLG (Maximum Contaminant Level Goal): The level of a contaminant in drinking water below, which there is no known or expected risk to health. MCLGs are set by the U.S. Environmental Protection Agency.

PHG (Public Health Goal): The level of a contaminant in drinking water below which there is no known or expected risk to health. PHGs are set by the California Environmental Protection Agency.

PDWS (Primary Drinking Water Standard): MCLs for contaminants that affect health along with their monitoring and reporting requirements, and water treatment requirements.

TT (**Treatment Technique**): A required process intended to reduce the level of a contaminant in drinking water.

NA: Not applicable.
ND: Not detected.

NS: No standard.

NTU (Nephelometric Turbidity Units): Measurement of the clarity, or turbidity, of water.

ppb (Parts Per Billion): One part per billion (or micrograms per liter).

ppm (Parts Per Million): One part per million (or milligrams per liter).

pCi/L (Picocuries Per Liter): A measure of the natural rate of radioactive disintegration.





STANISLAUS RIVER WATER

The City of Tracy is committed to providing a safe, reliable and affordable water supply to meet the needs of the community today and in the future. The City has participated with the cities of Manteca, Lathrop, Escalon and the South San Joaquin Irrigation District to bring high quality Sierra water from the Stanislaus River. This water source has increased the reliability of the City water supplies by having a third source of supply and provides redundancy in treatment facilities by having a second water treatment plant. Delivery of this water comprises the majority of water consumed in the City and is the only supply source used during the winter months.

CROSS CONNECTION PROTECTION

Backflow prevention assemblies are designed to allow water to flow into your home or office from the public water system but not allow water to flow in the reverse direction, creating effective cross connection protection. Reverse flow can carry untreatable pollutants and contaminants back to the public water system, compromising the water quality for all customers. Backflow prevention assemblies are required to be tested annually to ensure they are effectively protecting the public water system. If your residence has an active well on the premises or your business has fire sprinklers and/or landscaping, you should have a backflow prevention assembly. For questions regarding annual testing requirements, please call Erich Delmas, Laboratory Supervisor at (209) 831-4488.

WATER SOURCE ASSESSMENT

An assessment of the drinking water sources for the City of Tracy's water system was completed in June 2001. The sources are considered most vulnerable to the following activities: airports (maintenance and fueling areas), gas stations (historic and current), mining activities (historic and current), septic and waste landfill dumps (historic and current). You may request a copy of the assessment by contacting the Water Production Superintendent at (209) 831-6302.

The native groundwater under Tracy contains boron. Boron is a naturally occurring, non-carcinogenic, unregulated contaminant. Six of the City's wells contain elevated levels of boron. The City has minimized the use of groundwater and therefore minimized the amount of boron in the water supply.

SAMPLING RESULTS SHOWING TREATMENT OF SURFACE WATER SOURCES

<u>Treatment Technique:</u> A required process intended to reduce the level of a contaminant in drinking water (type of approved filtration technology used).

Turbidity of the filtered water must:

- Be less than or equal to 0.3 NTU in 95% of measurements in a month.
- Not exceed I NTU for more than eight consecutive hours.
- 3. Not exceed 3 NTU at any time.

Turbidity Performance Standards: Turbidity (measured in NTU) is a measurement of the cloudiness of water and is a good indicator of water quality and filtration performance. Turbidity results, which meet performance standards, are considered to be in compliance with filtration requirements (that must be met through the water treatment process).

Lowest monthly percentage of samples that met Turbidity Performance Standard No.1: 100%. Highest single turbidity measurement during 2009 was 0.18 NTU.

SAMPLING RESULTS SHOWING THE DETECTION OF LEAD AND COPPER										
Lead and Copper (To be completed only if there was a detection of lead or copper in the last sample set)	# Of Samples Collected	90TH Percentile Level Detected	# Sites Exceeding AL	AL	MCLG	Typical Source of Contaminant				
Lead (ppb)	41	1.3	0	15	2	Internal corrosion of household water plumbing systems; discharges from industrial manufacturers; erosion of natural deposits.				
Copper (ppm)	41	0.22	0	1.3	0.17	Internal corrosion of household water plumbing systems; erosion of natural deposits; leaching from wood preservatives.				

women and those with certain specific enzyme deficiencies. If you are caring for an infant, or if you are pregnant, you should ask advice from your health care provider ² Turbidity is a measure of the cloudiness of the water. We monitor it because it is a good indicator of water quality and the effectiveness of disinfectants.